



**ZORANTECH**  
卓然照明

## 350W constant current waterproof led driver



### ■ Features

- Constant Current (C.C.) output
- Built-in active PFC function, High efficiency up to 92%
- Input voltage/Full range(up to 305VAC)
- Protections:Short circuit/Over current/Over load/Over temperature
- Transformer copper wire is F class, Temperature up to 155°C
- THD≤15%(Bipolar), 5 years warranty
- Customizable dimming:0/1-10V or DALI or PWM
- Noise free, flicker free
- OEM & ODM, no MOQ, Support customization

### ■ Applications

- LED outdoor lighting
- LED landscape light
- LED architectural light
- LED street light
- LED flood light
- LED wall washer light
- LED high light
- LED underground light
- LED tunel light
- LED garden lights
- LED line light
- LED stage lights
- LED Spot light


### ■ Description

The constant current waterproof series produced by Zoran Technology is an AC-to-DC driver. operates from 90~305VAC and offers models with different rated voltage ranging ~between 20V and 200V. Thanks to the high efficiency up to 92%, with the fanless design, the entire series is able to operate for -40~ +80°C case temperature under free air convection. Dimming and other functions can be customized.


## ■ Electrical Specification

MODEL		ZR-HCM42NB-350W	ZR-HCM60NB-350W	ZR-HCM80NB-350W	ZR-HCM100NB-350W	ZR-HCM120NB-350W
Output	Output Voltage <small>Note.1</small>	27-42 VDC	43-60 VDC	60-80 VDC	80-100 VDC	100-120 VDC
	Output Current <small>Note.2</small>	8330 mA	5830 mA	4375 mA	3500 mA	2920 mA
	Rated Power	350 W	350 W	350 W	350 W	350 W
	Current Tolerance <small>Note.4</small>	±3%	±3%	±3%	±3%	±3%
	Auxiliary output(customizable)	12VDC	12VDC	12VDC	12VDC	12VDC
	Setup,Rise Time <small>Note.6</small>	500ms,100ms/115VAC 500ms,100ms/230VAC				
	Hold Up Time <small>(Typ.)</small>	10ms/115VAC 230VAC				
Input	Rate Voltage <small>Note.5</small>	90~265VAC or 100-277VAC				
	Frequency Range	48-62Hz				
	Power Factor	PF≥0.98/115VAC PF≥0.96/230VAC PF≥0.95/265VAC at full load				
	THD	THD≤15%(Bipolar)				
	Full load Efficiency	≥90%	≥90%	≥91%	≥91%	≥92%
	AC Current <small>(Typ.)</small>	3.35A/115VAC 1.68A/230VAC 1.44A/265VAC				
	No-load power consumption	≤1.0W				
Protection	Over Current	95-108%				
		Protection type:Constant current limiting,recovers automatically after fault condition is removed				
	Over Load	≤120% Recovers automatically after fault condition is removed				
	Short Circuit	Hiccup Mode,Recovers automatically after fault condition is removed				
	Over Temperature	Shut down O/P voltage,re-power on to recover				
Environment	Working Temperature	-40~+80 C (Refer to "Derating curve")				
	Max Case Temperature	+90 C				
	Working Humidity	20-95%RH non-condensing				
	Storage TEMP. Humidity	-40~+80 C 10-95%RH				
	TEMP. Coefficient	±0.03%/C (0-50 C)				
Safety & EMC	Safe Standards	U8750,CSA C22.2 No.250.13-12;ENEC AS/NZS IEC EN61347-1;AS/NZS IEC EN61347-2-13 independent EN62348;GB19510.14 IP65 or IP67				
	Withstand Voltage	I/P-O/P:3.75KVAC I/P-FG:2.0KVAC O/P-FG:1.0KVAC				
	Isolation Resistance	I/P-O/P,I/P-FG,O/P-FG:100M ohms/500VDC/25 C /70%RH				
	EMC Emission	Compliance to EN55015,EN61000-3-2 Class C(≥60% load);EN61000-3-3;GB17743;GB17625.1				
	EMC Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11;EN61547 heavy industry level(surge 4KV)				
Others	Dimension (L*W*H)	260*89*43 mm				
	Weight	2000g				
	Packing	10pcs/21kg/ctn				
Note	<p>1.All parameters Not specially mentioned are measured at 230VAC input, rated load and 25 C of ambient temperature.</p> <p>2.Ripple&amp;Noise are measured at 20MHz of bandwidth by using a 12"twisted pair-wire terminated with a 0.1uf &amp; 47uf parallel capacitor.</p> <p>3.Tolerance: includes set up tolerance, line regulation and load regulation.</p> <p>4.The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufactures must re-qualify EMC Directive on the complete installation again.</p> <p>5.Please refer to the product warranty on Zoran Technology website <a href="http://www.zorantech.com">http://www.zorantech.com</a>.</p> <p>6.If you need other special parameters, please contact our customer service for consultation!</p>					

■ Block Diagram




■ Mechanical Specification





- ※ The yellow-green wire at the input is the ground (FG), the brown wire is the AC phase wire(L), and blue wire is the AC neutral wire (N);
- ※ The red wire at the output is the positive output voltage(V+) and black wire is the negative output voltage(V-);
- ※ In addition, the length and thickness of the input and output lines can be customized according to customer requirements. Please contact Zoran Customer Service for details;


■ Life



■ Output load VS Temperature




■ Static characteristic curve




※ Derating output at low input voltage

■ PF characteristic curve

※ Tcase at 80°C



■ THD characteristic curve



■ Efficiency VS Load

